SOP-E021

CyAn/HyperCyt/Biomek

Objective: To make the HyperCyt sipper, the CyAn flow cytometer, and the Biomek robot all communicate in order to run a lot of plates .

Note: IP address of CyAn is: 128.210.61.239 IP address of HyperCyt is: 128.210.61.81

To find the IP address of the CyAn open a DOS wondow and type: ipconfig

CyAn- the CyAn needs to be turned on in a certain order anytime the computer is turned off, or if there is a strange problem.

- 1. Turn everything off.
 - a. The main power switch on the back of the CyAn
 - b. The main power switch on the right side of the SMS unit (sheath/waste tank system)
- 2. Shutdown the CyAn computer and turn power switch off.
- 3. Power up everything in this order (**order is critical**).
 - a. SMS power switch (right side)
 - b. CyAn main power switch (back of machine)
 - c. CyAn computer

HyperCyt- if the HyperCyt gets disconnected form the CyAn, the following steps need to be reset:

- 1. Open HyperCyt Controller software
- 2. Click on tools tab
- 3. select HyperCyt Options
- 4. Under Flow Cytometer Integration, need to check the box that says "enable flow cytometer integration". It should be on Cytometer Cyan, if not select Cyan from the dropdown menu.

| 5. save | | |
|--------------------------|------------------|-----------|
| | | |
| Created by: Kathy Ragheb | | |
| Verified by: | Date: 04/04/2011 | |
| Print Name | | Sign Name |